

DATA SHEET





HCSELF - 15W/M

Frost protection of pipes

This is a self-regulating heating cable designed to provide effective frost protection for pipes. The cable's self-regulating matrix lowers the heating effect of the cable as the temperature rises and, conversely, raises the heating effect at lower temperatures.


The cable can be fitted on the outside of pipes as traditional frost protection but also inside drain pipes and similar. When installing on the outside of plastic pipes, aluminium tape is applied along the entire length of the pipe. This will ensure good heat distribution.

It is recommended that the cable be controlled by means of a thermostat with a sensor mounted under the insulation.

The cable meets the requirements of IEC / EN 62395 for frost protection in private homes and industry.

Delivered on drum containing 250m cable.

TECHNICAL DATA	UK CE		
Nominal power	15 W/m @10 °C		
Supply voltage	230 V		
Cable dimensions	10,5 mm x 5 mm (+/-0,5 mm)		
Conductor insulation	Polyolefin		
Conductor dimension	2 x 0,56 mm ² , tinned		
Earthing	Aluminium Mylar tape with copper conductor		
Heating cable, outer sheath	Polyolefin, modified		
Colour	Black, RAL 9005 matte		
Permissible cable temperature	Max. 65 °C (85 °C afbrudt)		
Min. bending radius	30 mm, over the wide surface		
Warranty	5 years		
Minimum installation temperature	-15 °C		
Approval	CE · UKCA		
Standard	IEC/EN 62395		
Tolerance power @10° C	-10 %+20 %		



CONSTRUCTION

1	Conductor
2	Regulating Matrix
3	Conductor insulation
4	Earthing
5	Outer sheath

APPLICATIONS

Outside of pipe	\checkmark
Inside of pipe	

ACCESSORIES

Aluminum tape	
Thermostat	
Connection kit	

Version 2-072024

Heatcom Corporation A/S Barmstedt Allé 6 DK-5500 Middelfart Tel-4563 477 77






PRODUCT OVERVIEW



HCSELF - 15W/M

DESCRIPTION	OUTPUT@10°C	LENGTH
HCSELF, self-regulating heating cable, black	15 W/m	250m

MAX LENGTHS					
Start	On pipe		In drain pipes		
temperature	10 A	16 A	10 A	16 A	
10 °C	76 m	80 m	46 m	48 m	
0 °C	74 m	75 m	40 m	43 m	
-20 °C	66 m	66 m	28 m	32 m	



LINK TO OUR WEBSITE





Version 2-072024

Heatcom Corporation A/S Barmstedt Allé 6 DK-5500 Middelfart Tel. +45 63 41 77 77 Sales@Heatcom.dk

