



## THERMOSTAT HC200 UNI

Universal, programmable (indoor/outdoor)

HC200 Uni has been developed by Heatcom to be used for many different applications.

The thermostat is placed directly in the power outlet indoors or outdoors, and the heat source can be plugged directly into the thermostat's Schuko power outlet.

Alternatively, it is possible to install the heat source without a plug behind the thermostat.

The included temperature sensor is already fitted with a 3 m cable and can be placed where the temperature needs to be regulated.

Frost protection can be managed without any adjustment of the thermostat, just place the sensor and connect the heat source.

The thermostat can be used both for frost protection and for controlling heating in, for example, greenhouses, orangeries or outbuildings. Here, programming with 4 daily events offers great advantages.



### ADVANTAGES

- Universal
- 3 metre sensor
- Programmable
- IP44
- Plug 'n' play



Version 2-102023

Heatcom Corporation A/S  
Barmstedt Allé 6  
5500 Middelfart  
Tel. +45 63 41 77 77  
Sales@Heatcom.dk



# THERMOSTAT HC200 UNI

## Universal, programmable (indoor/outdoor)

HC200 UNI is a thermostat that plugs directly into the power outlet and, together with a heat source, will provide effective frost protection without any additional configuration.

When placed outdoors in a suitable power outlet, the thermostat will have an IP44 rating. Furthermore, it is possible to install a heat source directly behind the thermostat and achieve even better protection against water.

The included temperature sensor is already fitted with a 3 m cable and can be placed where the temperature needs to be regulated. The thermostat is set using the high-visibility display and 3 buttons on the front.

If there are different heating requirements at different times of the day, you can set 4 daily events and thus include, for example, night-time temperature reduction.

The thermostat has a built-in alarm that can be shown on the display, but there is the option of an audible alarm to be emitted if the set temperature is not reached.



### TECHNICAL DATA

Supply voltage	230 V – 50–60 Hz
Maximum load	3000 W
IP class	IP44 (connected)
Temperature range	+1° C ... +70 °C
Sensor	10 KΩ @ 25°C, length 3 m
Screen	1.6" backlit LCD
Colour	Matte black
Installation	Schuko socket
Dimensions	125 x 64 x 40 mm (H x W x D)
Warranty	3 years
Approvals	CE / RoHS

### FUNCTIONS

- Frost protection
- Room heating
- Low temperature alarm
- 4 timed events
- Safe mode in case of error
- Backlit display

### LINK TO OUR WEBSITE



Version 2-102023

Heatcom Corporation A/S  
Barmstedt Allé 6  
5500 Middelfart  
Tel. +45 63 41 77 77  
Sales@Heatcom.dk